



7505 40 St SE  
Calgary AB T2C 2H5  
Phone 403.279.4170  
Fax 403.236.1707  
[www.geogROUT.com](http://www.geogROUT.com)

## **IMPORTANT NOTICE**

### **RE: CONCRETE MAINTENANCE IN YOUR AREA**

#### **Tentative Start Date:**

#### **Dear Resident,**

The Land Developer for your area has contracted Geo Grout Inc. to raise settled concrete curbs and sidewalks to design grade, as per City of Calgary specifications. Geo Grout Inc. will be in your subdivision to begin this work on or shortly after the start date noted. If your private sidewalk or driveway is adjacent to a noted settlement it may also require lifting to remove any tripping hazard created after raising the City sidewalk. The lifting process, known as slab jacking, involves coring 40 mm diameter holes through the sidewalk or driveway to facilitate the lifting process. The slab jacking procedure takes approximately 40 minutes per location to complete and your sidewalk or driveway should be accessible within a few hours of completion.

The core holes will be temporarily plugged after lifting to allow the slab jacking grout to set. A permanent repair of the core holes will be performed shortly after the slab jacking work in your area is completed. Standard concrete driveways and sidewalks will have the core holes repaired to match the original appearance of the concrete. For exposed aggregate and stamped concrete driveways and sidewalks the cores are saved so they can be placed back in the driveway or sidewalk holes then patched in around the core.

Should you have any questions or concerns, please visit our website at [www.geogROUT.com](http://www.geogROUT.com)



7505 40 St SE  
Calgary AB T2C 2H5  
Phone 403.279.4170  
Fax 403.236.1707  
[www.geogrout.com](http://www.geogrout.com)

## **IMPORTANT NOTICE**

### **RE: CONCRETE MAINTENANCE IN YOUR AREA**

**Tentative Start Date: Monday, July 1, 2019**

**Dear Resident,**

The Land Developer for your area has contracted Geo Grout Inc. to raise settled concrete curbs and sidewalks to design grade, as per City of Calgary specifications. Geo Grout Inc. will be in your subdivision to begin this work on or shortly after the start date noted. If your private sidewalk or driveway is adjacent to a noted settlement it may also require lifting to remove any tripping hazard created after raising the City sidewalk. The lifting process, known as slab jacking, involves coring 40 mm diameter holes through the sidewalk or driveway to facilitate the lifting process. The slab jacking procedure takes approximately 40 minutes per location to complete and your sidewalk or driveway should be accessible within a few hours of completion.

The core holes will be temporarily plugged after lifting to allow the slab jacking grout to set. A permanent repair of the core holes will be performed shortly after the slab jacking work in your area is completed. Standard concrete driveways and sidewalks will have the core holes repaired to match the original appearance of the concrete. For exposed aggregate and stamped concrete driveways and sidewalks the cores are saved so they can be placed back in the driveway or sidewalk holes then patched in around the core.

Should you have any questions or concerns, please visit our website at

[www.geogrout.com](http://www.geogrout.com)